

Optional Face Fin

2-5/16"



Commercial Aluminum Awning AP-C50

Standard Features

- Flush sash to frame construction
- 2-5/8" Frame Depth
- T-6063 Aluminum Extrusions with .062" walls
- Thermally Broken Frame and Sash
- Factory Glazed with 7/8" Insulated Glass with Super Spacer® warm edge spacer technology for superior thermal performance.
- Concealed Hinge system for a modern look
- Equal Leg Frame
- Triple Weatherseals
- Interior Glazed Field Servicable
- Architectural paint finish meets AAMA 2603. Colors available for normal lead times: White, Bronze, and Clear Anodized. For large projects, custom colors are available on a special order basis – please contact our office for details.
- Truth Maxim® Hardware with E-Gard™ Coating features enhanced corrosion protection
- Roto Operator or Push-Out models
- Sleek, Low-Profile Lock and Operator system
- Single-Point or Multi-Point Locking System assures a weather-tight lock between the sash and frame.

Optional Features

- Extruded Interior Screen eliminates unsightly wicket type screens (not available on push-out model).
- Numerous high performance glazing options
- Mullion for multiple units
- Many Grid Between Glass (GBG) configurations are available for greater design flexibility and low maintenance.
- Stainless Steel Hardware
- Stainless Steel Support Arms
- Optional Nailing Fin and Face Flange

The Westco Awning is a heavy-duty aluminum light commercial projection window with a distinctly residential look and feel. Drawing on our many years of residential and light commercial window experience, we have developed a completely new product that blends the pleasing aesthetic appeal and ease of operation of residential windows with the rugged serviceability and performance of thermally broken commercial aluminum. The Westco Projection Series of products rounds out our very popular Westco Single Hung, Slider, and Fixed window lines which have been used in numerous schools, hotels, and other commercial and residential applications for many years.

3-5/16"

7/16"

2-5/8'