





Commercial Aluminum Double Hung H-C45

Standard Features

- 3-1/4" Frame Depth
- T-6063 Aluminum Extrusions with .062" walls
- Thermally Broken Frame and Sash
- Factory Glazed with 7/8" Insulated Glass with Super Spacer[®] warm edge spacer technology for superior thermal performance.
- Zinc die-cast Cam Locks, 2 locks standard over 24" in width
- Replacement or New Construction Frames
- Finseal Weatherseals on both sashes with two rubber bulbs at the frame sill, and four weatherstrips at the interlock.
- Both sashes tilt in for easy cleaning if desired.
- Architectural paint finish meets AAMA 2603. Colors available for normal lead times: White, Bronze, and Tan. For large projects, custom colors are available on a special order basis – please contact our office for details.
- Concealed Spiral Balances for quiet, low-friction operation. Commercial Heavy Duty Balances are available for most large size windows.
- Strong Extruded Aluminum bottom lift rail
- Available with nail fin for new construction or without nail fin for replacement applications.
- Sill Angle for sloped sill replacement applications and Head Expanders are available.

Optional Features

- Extruded Aluminum Full or Half Screen for long service life
- Numerous high performance glazing options
- Mullion for multiple units
- Many Grid Between Glass (GBG) configurations are available for greater design flexibility and low maintenance.
- Extruded Aluminum Muntin to divide top sash is especially useful for concealing drop type ceilings.

The West-Prime Thermal Double Hung window is ideally suited for commercial use. Designed to handle the demanding requirements of commercial quality windows, the West-Prime Thermal maintains a pleasing, easy-to-operate residential look and feel. The West-Prime Commercial Aluminum Series, consisting of Double Hung and Fixed windows, are a perfect complement to the Westco Commercial Aluminum Series, both of which can be custom manufactured to your specifications, delivered in a timely manner, and can help make your project a complete success.